



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : B65D 6/24, 21/08	A1	(11) International Publication Number: WO 94/11258 (43) International Publication Date: 26 May 1994 (26.05.94)
---	----	---

(21) International Application Number: PCT/US93/10765

(22) International Filing Date: 9 November 1993 (09.11.93)

(30) Priority data:
07/974,206 10 November 1992 (10.11.92) US

(71) Applicant: THE AMERICAN TEAM [US/US]; 42050 Executive Drive, Mt. Clemens, MI 48045 (US).


(72) Inventors: MARCHI, Mitchell, M. ; 2879 Aldgate Drive, Bloomfield Hills, MI 48304 (US). BLANKENBURG, Karl ; 32131 Claeys Drive, Warren, MI 48093 (US).

(74) Agents: HANLON, William, M., Jr. et al.; Basile and Hanlon, 1650 West Big Beaver Road, Suite 210, Troy, MI 48084 (US).

(81) Designated States: CA, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published
With international search report.

(54) Title: RECONFIGURABLE ARTICLE STORAGE CONTAINER



(57) Abstract

A reconfigurable article storage container includes a plurality of identical panels (20), each including at least two slots (46, 47) formed by connector webs (40) integrally formed with and extending between adjacent panels sections (22, 24, 26). Certain panels (20A, 20C) are invertible 180 degrees and oriented perpendicular to adjacent panels (20B, 20D) such that interconnecting slots (46, 47) formed by the connector webs (40) between adjacent panel sections (22, 24, 26) can be slidably engaged to form any polygonal or irregular shaped storage container (10) having any number and size of individual storage compartments (16) formed between certain of the interconnected panels. Edge connectors (60) interconnect the ends of two panels (20) in a colinear arrangement to increase the length of any wall. Vertical connectors (70) are insertable into aligned slots (46, 47) formed between the connector webs (40) of two stacked panels (20B, 20E) and extend between the two panels (20B, 20E) to join them in a vertical stack arrangement to increase the height of any wall.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

RECONFIGURABLE ARTICLE STORAGE CONTAINER

BACKGROUND OF THE INVENTIONField of the Invention:

5 The present invention relates, in general, to article storage containers, and specifically, for article storage containers for use in vehicle storage compartments.

Description of the Art:

10 Trunks, storage compartments and beds of vehicles, trucks, vans, etc., are designed with a large open area between the surrounding vehicle body structure and the underlying floor to receive various articles or cargo therein. Oftentimes, small articles, such as grocery bags, bottles, and loose articles not in bags or boxes are
15 placed in a vehicle trunk or storage compartment. Such small articles are susceptible to movement during operation of the vehicle which can result in noise and damage to the articles and/or the vehicle.

20 In an effort to overcome this problem, netting has been secured to the rear wall panel of vehicle trunks and supported via elastic straps to provide an expandable compartment for receiving such small items, such as grocery bags, bottles, etc. However, the netting extends openly across the width of the trunk and is not capable of
25 preventing movement of such articles laterally across the width of the trunk. Such netting is also expandable by only a small distance so as to be able to receive a limited number of articles therein.

30 Fixed article containers have also been designed for use in vehicle trunks or storage compartments. Such containers are typically provided with a fixed overall dimension or size and include a number of individual compartments therein. Certain of these containers are provided with removable dividers so as to enable the
35 individual storage compartments to be adjusted in size to receive various sized articles. Such article containers have also been provided in a foldable or collapsible form so as to be able to collapsed to a small volume, non-use

position. Generally, however, such fixed article containers have a predetermined outer peripheral size, even if the individual storage compartments are adjustable by means of movable dividers. As such, such fixed size
5 containers consume a majority of the space available in a vehicle trunk or storage area.

United States Patent No. 5,052,580 to Khoury discloses a vehicle cargo storage organizer formed of a plurality of first and second sized wall panels which are
10 interconnectible in various arrangements to form individual storage compartments therebetween for storing articles. Each of the first and second sets of wall panels is provided with slots arranged alternately and oppositely in a spaced-apart manner along the length and opposite side
15 edges of each wall panel. Any two wall panels may be interconnected to each other by sliding adjoining slots of the two wall panels together when the wall panels are arranged in a perpendicular orientation with respect to each other. Elastic cords with resilient bulb ends may be
20 attached between ports formed on each of the wall panels to connect two of the wall panels together.

While the Khoury vehicle cargo storage organizer may be reconfigured to provide individual article storage compartments of a predetermined size and in a predetermined
25 number to suit the needs of a user or to fit within a particular size vehicle storage compartment, such an organizer is provided with two different sized wall panels. This increases the overall cost of such a vehicle cargo storage organizer as a number of different parts must be
30 manufactured for the organizer. In addition, assembly of the cargo storage organizer is more complicated since thought and time must be expended by a user to determine exactly where each of the different wall panels can be optimally positioned.

35 Thus, it would be desirable to provide an article storage container for vehicles which may be easily reconfigurable in overall size and shape and with the

desired number and size of individual storage compartments formed therein. It would also be desirable to provide an article storage container which may be reconfigurable into different arrangements and number and size of individual storage compartments while using only a number of identical, single size panels. Finally, it would be desirable to provide an article storage container using a number of identically shaped panels which can be interconnected end-to-end to increase the overall length or width of the article storage container as well as being interconnectible at top and bottom edges to increase the overall height of the container or certain compartments of the container.

SUMMARY OF THE INVENTION

The present invention is a reconfigurable article storage container particularly suited for use in transporting articles in a storage compartment of a vehicle, such as an automobile, truck, van, etc.

The article container of the present invention includes a plurality of like shaped and sized panels which are interconnectible into a container of selectable size and shape to form a plurality of individual storage compartments therein. Each panel includes first and second spaced edges and first and second side ends. In a preferred embodiment, each panel is formed of a plurality of panel sections of like height, each having first and second spaced edges co-linearly arranged with the first and second edges of adjacent panel sections. The opposed side ends of each of the panel sections are spaced from the side ends of adjacent panel sections. A connector web is integrally formed with the panel sections and is disposed between two adjacent panel sections. Each connector web has a predetermined length and is spaced a predetermined distance from the second edge of two adjacent panel sections.

Each connector web forms a connector slot between two adjacent panel sections, the connector web itself and the second edges of two adjacent panel sections for releasably receiving a connector slot of another panel therein when the other panel is inverted 180° and oriented perpendicular to a first panel.

In a preferred embodiment, each panel is formed with at least three main panel sections including a centrally located panel section having the largest overall length and two outermost panel sections being of a shorter length and either having the same or identical length with respect to each other. Connector webs are integrally formed between the three panel sections. Preferably, all of the panel sections and connecting web are integrally formed as a one-piece, unitary member from molded plastic.

Preferably, the side ends of each of the panel sections are provided in a predetermined polygonal configuration, such as a partial hexagonal edge configuration in which a plurality of individual side edge faces are disposed at an interior angle of less than 90° with respect to adjacent side edge faces. This angular arrangement of side edge faces which extends between the first and second edges of each of the panel sections forms a mating surface when two panels are interconnected in a perpendicular arrangement such that the side end faces of one panel adjacent to a particular connector slot are disposed in registry with the corresponding side end faces of the interconnecting panel.

A side end connector means is releasably attachable to the outermost side ends of two panels for connecting two panels in a lengthwise extending, co-planar arrangement to increase the overall length of any wall of the article storage container of the present invention. The side end connector means preferably comprises a connector member having outwardly extending pairs of spaced legs which are complementarily formed to the exterior shape of the panel sections so as to be releasably slid over the

side end portions of two co-linearly arranged panels to connect such panels together.

Further, a vertical connector means may be provided for interconnecting two panels in a vertically stacked arrangement. The vertical connector means preferably comprises a plug configured to be releasably engageable in a connector slot formed between the connecting web and two adjacent panel sections of a panel and having a length such that a portion thereof extends outward from the panel. The outwardly extending portion is releasably engageable in a connector slot formed between adjacent panel sections of another panel so as to interconnect such panels in a co-planar, vertically extending wall.

The reconfigurable article storage container of the present invention overcomes many of the problems encountered with previously devised vehicle article storage containers in that it may be easily reconfigurable to fit the dimensions of any vehicle storage compartment as well as easily reconfigurable to receive any number of different sized and shaped articles in individual storage compartments which may be provided in any number and any size corresponding to the articles to be transported. The article storage container of the present invention is also easily disassembled for convenient storage when not in use.

The present article storage container has a low manufacturing cost since it is formed essentially of a number of identically constructed panels. Since the panels are preferably formed of molded plastic, only a single mold is required to form all of the necessary panels for a complete article storage container. By means of simple side end connectors and vertical connectors, a number of like panels may be connected end-to-end and/or vertically in a stacked arrangement to increase the overall length or height of any of the walls of the complete article storage container.

BRIEF DESCRIPTION OF THE DRAWING

The various features, advantages and other uses of the present invention will become more apparent by referring to the following detailed description and drawing in which:

Figure 1 is a perspective view of an article storage container of the present invention shown mounted in the trunk of an automobile;

Figure 2 is a perspective view of one of the identical panels used in the article storage container shown in Figure 1;

Figure 3 is an exploded, perspective view showing the interconnection of a number of like panels of the article storage container of the present invention;

Figure 4 is a plan view of the side end connector means interconnecting two panels in a lengthwise, co-planar arrangement as generally shown in Figure 3;

Figure 5 is a cross sectional view generally taken along line 5-5 in Figure 3; and

Figure 6 is a perspective view of a vertical connector means shown generally in Figure 3.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

As shown in the drawing, the present invention is a reconfigurable article storage container 10 which is designed for removable installation as well as assembly and disassembly within a vehicle storage compartment, such as the trunk 12 of an automobile 14, as shown in Figure 1, as well as the storage compartments of trucks, vans and the like. The article storage container 10 is designed to be reconfigured into any overall dimensional size as well as with any number and size of individual article storage compartments 16. Each article storage compartment 16 may be precisely configured to receive various sized and number of articles therein to prevent such articles from moving freely throughout the vehicle storage compartment 12 so as

to prevent damage to the articles as well as to the surrounding vehicle body structure.

The article storage container 10 of the present invention is formed of a plurality of identical panels, each denoted by reference number 20. One of the identical panels 20 is shown in greater detail in Figure 2. The panel 20 is preferably formed as a one-piece, unitary member of a suitable lightweight material, such as a molded plastic. Preferably, each panel 20 is formed of a thermoplastic, such as, for example, polypropylene, polystyrene, etc. Each panel 20 may have any overall height, width or depth dimension.

According to a preferred embodiment of the present invention, each panel 20 is provided with a predetermined number of individual panel sections, such as a first or central panel section 22 and a pair of outer panel sections 24 and 26. Each of the panel sections 22, 24 and 26 has the same identical height between a first edge 28 and an opposed, spaced second edge 30. By way of example only, the first panel section 22 has a longer length than the two outermost panel sections 24 and 26. The outermost panel sections 24 and 26, while shown as having identical lengths, may also be provided in unequal lengths if desired. Each of the panel sections 22, 24 and 26 also includes opposed side ends 32 and 34 which extend between the first and second edges 28 and 30.

By way of example only, each of the side edges 32 and 34 of each of the panel sections 22, 24 and 26 of the panel 20 is formed in a predetermined polygonal shape, such as a three-sided shape shown in Figure 2. This forms a number of side end faces, all denoted generally by reference number 36 in Figure 2, which have an interior angle respectively therebetween of less than 90°. The reason for this angular arrangement of the side end faces 36 will become more apparent hereafter.

A connector web 40 is integrally formed with the panel sections 22, 24 and 26 and is disposed between two

adjacent panel sections, such as the connector web 40 disposed between and integrally formed with the panel sections 22 and 24 and a similar connector web 40 joined to and extending between the other side end 32 of the panel section 22 and the side end 34 of the panel section 26. Each of the connector webs 40 is identically constructed and is provided in a predetermined length between a first end 42 and a second end 44. The second end 44 of each connector web 40 is spaced from the second edge 30 of the two adjacent panel sections, such as the panel sections 22 and 24 shown in Figure 2, to form a slot therebetween of a predetermined length, as denoted generally by reference number 46. The length of the slot 46 is preferably one-half of the height of the panel 20. The slot 46 extends from the spaced second edges 30 of two adjacent panel sections, such as panel sections 22 and 24, to the second end 44 of the connector web 40. The slot 46 acts as an interconnecting means to join two identical panels 20 together.

Another slot 47 is formed between the first end 42 of each connector web 40 and the adjacent first edge 28 of each panel section. As the first end 42 of the connector web 40 is closer to the adjacent edge of the panel 20, the slot 47 is shorter than the slot 46.

Each connector web 40 has a width approximately equal to the width of the side end face 36 to which the connector web 40 is attached. This forms a rigid fit between two panels 20 as described hereafter.

By way of example only, each panel 20 also includes outermost end panel sections 50 and 52 which are identically constructed, although each has a smaller overall cross section than the adjacent panel sections 24 and 26. Connector webs 40 are integrally joined to and extend between each of the end panel sections 50 and 52 and the adjacent panel sections 24 and 26, respectively. Interconnecting slots 46 are also formed between the adjacent disposed end panel section 50 and panel section 24

and the end panel section 52 and the adjacent panel section 26. This arrangement provide four interconnecting slots 46 along the length of each panel 20 for receiving another panel or panels therein in an interconnecting arrangement, as described hereafter. This may be employed by a user to vary the size and shape of the individual storage compartments formed between a number of interconnected panels 20 as well as the overall size and shape of the complete article storage container 10.

Figure 3 shows the interconnection of a number of like panels 20 into the overall article storage container 10. It will be understood that only a portion of the complete article storage container 10 is shown in Figure 3. Further, for reasons of clarity, each identical panel 20 is depicted by a different reference numeral, such as 20, 20A, 20B, 20C, 20D, 20E and 20F, so as to be able to differentiate between the orientation and position of each identical panel 20. In interconnecting each panel 20 to one or more other panels 20, a first panel 20, as shown in Figure 3, will be oriented in such a manner that the interconnecting slots 46 formed by the connector webs 40 between adjacent panel sections 22, 24 and 26 will be extending downward. It will be understood that this orientation is by way of example only as the panel 20 could be inverted with the interconnecting slot 46 extending upward.

A second panel 20A is inverted 180° from the orientation of the first panel 20 and positioned perpendicular to the first panel 20 as shown in Figure 3. In this orientation, the connecting slots 46 in the second panel 20A extend upward from the respective connector webs 40 in an opposite direction from the corresponding connecting slots 46 in the first panel 20. The two panels 20 and 20A are urged together by sliding one of the connecting slots 46 in the second panel 20A through one of the connecting slots 46 in the first panel 20 as shown in Figure 3 until the connecting webs 40 on each of the panels

20 and 20A in the respective connecting slots 46 are disposed in contact with each other. Since a panel section on each of the panels 20 and 20A extends outward from the joint of two interconnected slots 46, the two panels 20 and 20A are held in a fixed, perpendicular orientation with respect to each other. This rigid engagement between two panels, such as panels 20 and 20A, is enhanced by the angular side end faces of each panel section which securely engages the side end faces of the interconnected panel. At the same time, the panels 20 and 20A may be easily separated for repositioning or storage.

Panel 20C is oriented in the same manner as panel 20A with the interconnecting slots 46 formed therein extending upward from the respective connector webs 40. The panel 20C may be interconnected to a slot 46 in the first panel 20, such as at the interconnecting slots 46 formed between an end panel section 50 of each of the panels 20 and 20C and the adjoining panel section 24. Panel 20B may be interconnected between the panels 20A and 20C in a similar manner by means of the connecting slots 46. The panel 20B is oriented in the same manner as the panel 20 with the interconnecting slots 46 formed therein extending downward as shown in Figure 3. It should be noted that the interconnection of the panel 20A to the panels 20 and 20B is at the interconnecting slot 26 formed between the first panel section 22 of each of the panels 20 and 20B and the adjacent panel section 26 of each of the panels 20 and 20B.

The thus described interconnection of the panels 20, 20A, 20B and 20C forms a rectangular box in which the interior thereof forms an article storage compartment denoted by reference number 16. The size of the storage compartment 16 could be varied by using a different slot 46 for interconnecting two panels 20.

Another feature of the present invention is shown in Figure 5 in which a suitable fastening means 54 is employed to releasably hold the entire article storage

container 10 in a fixed position in a vehicle storage compartment 12. The fastener 54, in an exemplary embodiment, comprises a VELCRO-type fastener which is releasably engageable with the type of carpeting typically found in an automobile trunk or storage compartment. In this manner, once the article storage container 10 has been configured to the desired shape and with the desired number and size of individual storage compartments 16, the fasteners 54 which may be provided on the second edges 30 of certain of the panels 20 may be employed to retain the article container 10 in a fixed position without any movement during operation of the vehicle.

Another feature of the present invention is shown in Figure 3 and in greater detail in Figure 4. This feature involves a length extender in the form of a side edge connector means 60. The side edge connector means 60 is a body having a central solid portion 62 which is slidably disposable in the space formed between two adjacent, side end to side end positioned panels, such as panels 20 and 20D shown in Figures 3 and 4. A pair of spaced legs 64 and 66 extends outward from each side of the central portion 62. The legs in each pair of legs 64 and 66 are spaced apart and have a configuration complementary to the exterior configuration of adjacent disposed panel sections, such as panel sections 24 and 50 in the panel 20D and the panel sections 50 and 26 in the panel 20. As noted above, a polygonal shape is provided on the side edges of each of the panel sections of each panel and includes individual side edge faces 36. The legs 64 and 66 of each pair of legs on the connector 60 are formed at similar angles so as to releasably engage and retain adjacently disposed side ends of two panels, such as panels 20 and 20D, in an end-to-end lengthwise extending, co-linear arrangement. In this manner, any number of panels 20 may be interconnected end-to-end to increase the overall length of any of the side walls or intermediate walls of the article container 10. It should be noted that the side

edge connector means 60 has the same length as that of the panels 20. A shorter length may also be employed.

A vertical connector means denoted by reference number 70 in Figures 3 and 5 may also be provided for
5 connecting two panels, such as panels 20B and 20E, in a vertical, co-planar stacked arrangement to increase the overall height of any wall of the article storage container 10. The vertical connector means 70 is in the form of a solid body having opposed ends 72 and 74 interconnected by
10 a reduced width central portion 76. The opposed faces or side edges of the vertical connector 70 are formed in an angular or faceted arrangement complementary to the polygonal shape of the side ends of the panel sections of each of the panels 20. In this manner, the vertical
15 connector 70 may be slid into a slot 47 formed between the first end 42 of the connector web 40 on certain of the panels, such as panel 20B, and is held in place between the adjoining side edges of the panel sections 50 and 26, as shown in Figure 3.

20 A portion of the connector member 70 extends outward above the first edge 28 of the panel 20B a distance equal to the length of the slots 46 so as to releasably engage a slot 46 formed in a like panel member 20E which is inverted 180° in orientation from the panel 20B. The
25 outwardly extending portion of the vertical connector 70 engages the side edges of the panel sections 50 and 26 of the panel 20E to securely connect the panels 20B and 20E together in a vertical, co-planar, stacked arrangement.

Another feature of the present invention is shown
30 in Figure 2 in which weight reducing cutouts in the form of apertures 84 are formed in certain portions of the panel sections 22, 24 and 26 of each panel 20. The apertures 84 are illustrated as having a square configuration by way of example only. It will be understood that the shape of the
35 apertures 84 as well as their number may be varied to meet the needs of a particular application while retaining

sufficient strength for the panel 20. Similar cutouts 86 are formed in each of the connector webs 40.

Further, the end panel sections 50 and 52 of each panel 20 have an open outer end, also for weight reducing purposes. Each end panel section 50 and 52 is provided with a side edge with the predetermined angular side edge faces described above and an outer wall 88. However, the remaining sides of each end panel section 50 and 52 are open. A plurality of ribs 90 may be spaced along the length of each end panel section 50 and 52 for rigidity.

In summary, there has been disclosed a unique article storage container designed particularly for use in vehicle storage compartments. The article storage container is easily reconfigurable to different overall configurations and dimensions to suit the particular space requirements of a vehicle storage compartment as well as to provide any number and size of individual article storage compartments therein. The article storage container of the present invention is easily assembled and disassembled. Further, the article storage container is formed of a number of identically constructed panels which reduces manufacturing costs and simplifies the assembly of the article storage container into the desired configuration since only single size panels need be manipulated by the user.

What is Claimed is:

1 1. A reconfigurable article storage container
2 comprising:

3 a plurality of identical panels interconnectible
4 into a container of variably arrangeable size and number of
5 panels and containing at least one individual article
6 storage area adjacent at least one of the panels therein,
7 each panel including:

8 a plurality of panel sections of identical
9 height, each panel section having first and second
10 spaced edges thereof co-linearly arranged with the
11 first and second edges of adjacent panel sections,
12 each panel section having first and second side ends
13 spaced from the first and second side ends of an
14 adjacent panel section;

15 a connector web integrally formed with and
16 disposed between the side ends of two adjacent panel
17 sections, each connector web being of a predetermined
18 length and having one end spaced a predetermined
19 distance from the one of the first and second edges of
20 the adjacent panel sections; and

21 a connector slot formed between two
22 adjacent panel sections and extending from the one of
23 the first and second edges of the adjacent panel
24 sections to the one end of the connector web, the
25 connector slot releasably receiving the first
26 connector slot of another panel therein, the another
27 panel being inverted 180° and oriented perpendicular
28 to a connected panel.

1 2. The reconfigurable article storage container
2 of Claim 1 wherein:

3 another end of each connector web is spaced from
4 the first edge of the adjacent panel sections by a
5 predetermined distance less than the distance between the

6 one end of the connector web and the second edge of the
7 adjacent panel sections.

1 3. The reconfigurable article storage container
2 of Claim 1 wherein:

3 the panel sections and the connector webs of each
4 panel are formed as a one-piece, integrally constructed
5 member.

1 4. The reconfigurable article storage container
2 of Claim 3 wherein each panel is formed of molded plastic.

1 5. The reconfigurable article storage container
2 of Claim 1 wherein the panel sections of each panel
3 comprises:

4 a first panel section of a first predetermined
5 length; and

6 two second panel sections having a length
7 different from the length of the first panel section and
8 disposed adjacent to opposite side ends of the first panel
9 section and connected thereto by connector webs.

1 6. The reconfigurable article storage container
2 of Claim 5 wherein each second panel section has a shorter
3 length than the first panel section.

1 7. The reconfigurable article storage container
2 of Claim 5 wherein each panel further comprises:

3 first and second end panel sections, each
4 attached by a connector web to one of the second panel
5 sections; and

6 identical, spaced connector slots formed between
7 each of the first and second end panel section, the
8 adjacent one of the second panel sections and the connector
9 web therebetween.

1 8. The reconfigurable article storage container
2 of Claim 1 further including:
3 weight reducing apertures of a predetermined size
4 and shape formed in a major portion of the surface area of
5 each panel section.

1 9. The reconfigurable article storage container
2 of Claim 1 further including:
3 side end connector means, releasably attachable
4 to outermost side ends of two adjacently disposed panels,
5 for connecting the two panels in a lengthwise extending,
6 co-planar arrangement.

1 10. The reconfigurable article storage container
2 of Claim 1 wherein:
3 the side ends of each panel section have a
4 polygonal shape to form side end faces engageable with
5 identical side end faces of an identical panel when the two
6 panels are interconnected in a perpendicular, inverted
7 arrangement.

1 11. The reconfigurable article storage container
2 of Claim 10 further including:
3 side end connector means, releasably attachable
4 to outermost side ends of two panels, for connecting the
5 two panels in a lengthwise extending, co-planar
6 arrangement;
7 the side end connector means having first and
8 second end portions formed of spaced first and second legs,
9 the first and second legs having a shape complimentary to
10 the shape of the side ends of the panels for releasably
11 engaging the side ends of the panels.

1 12. The reconfigurable article storage container
2 of Claim 11 wherein the side end connector means further
3 comprises:

4 a central leg extending between the first and
5 second end portions and insertable between the outermost
6 ends of two co-linearly arranged panels.

1 13. The reconfigurable article storage container
2 of Claim 1 further including:

3 vertical connector means, mountable in two
4 vertically aligned connector slots formed between a
5 connector web and one of the first and second edges of each
6 of two vertically disposed panel sections and extending
7 outward from one panel into the other panel, for releasably
8 engaging and interconnecting the two panels in a stacked,
9 vertical, co-planar arrangement.

1 14. The reconfigurable article storage container
2 of Claim 13 wherein the vertical connector means comprises:

3 a body having an exterior surface shaped
4 complementary to the shape of the side end faces of the
5 panel sections to releasably engage the side end faces of
6 two edge-to-edge disposed panels.

1 15. The reconfigurable article storage container
2 of Claim 1 wherein:

3 each connector web has a thickness less than the
4 thickness of the panel sections.

1 16. The reconfigurable article storage container
2 of Claim 1 further comprising:

3 the connector slot having a length equal to one-
4 half of the distance between the first and second edges of
5 the adjacent panel sections and formed between two adjacent
6 panel sections and extending from the first edges of the
7 two adjacent panel sections to a second end of the
8 connector web.

1 17. The reconfigurable article storage container
2 of Claim 1 further comprising:

3 the connector web having a second end spaced a
4 predetermined distance from the second edges of the
5 adjacent panel sections and a first end spaced from the
6 first edges of the adjacent panel sections by a
7 predetermined distance less than the distance between the
8 second end of the connector web and the second edges of the
9 adjacent panel sections; and
10 a first connector slot formed between two
11 adjacent panel sections and extending from the first edges
12 of the adjacent panel sections to the first end of the
13 connector web, and a second connector slot formed between
14 two adjacent panel sections and extending from the first
15 edges of the two adjacent panel sections to the second end
16 of the connector web;
17 the second connector slot of one panel releasably
18 receiving a second connector slot of another panel therein,
19 the another panel being inverted 180° and oriented
20 perpendicular to the one panel, each second connector slot
21 having a length equal to one-half of the distance between
22 the first and second edges of the adjacent panel sections.

1 18. The reconfigurable article storage container
2 of Claim 17 further comprising:
3 the panel sections and the connector webs for
4 each panel being formed as a one-piece, integrally
5 constructed member;
6 the panel sections comprising:
7 a first panel section of a first
8 predetermined length;
9 two second panel sections having a length
10 different from the length of the first panel section
11 and disposed adjacent to opposite side ends of the
12 first panel section and connected thereto by connector
13 webs; and
14 first and second end panel sections, each
15 attached by a connector web to one of the second panel
16 sections; and

17 the first and second connector slots being formed
18 by each connector web between each end of the first panel
19 section and each adjacent second end panel section and
20 between each second panel section and the adjacent one of
21 the first and second end panel sections.

1 19. The reconfigurable article storage container
2 of Claim 18 wherein each panel is formed of molded plastic.

1 20. The reconfigurable article storage container
2 of Claim 17 further including:

3 weight reducing apertures of a predetermined size
4 and shape formed in a major portion of the surface area of
5 each panel section.

1 21. The reconfigurable article storage container
2 of Claim 17 further including:

3 side end connector means, releasably attachable
4 to outermost side ends of two adjacently disposed, co-
5 planar arranged panels, for connecting the two panels in a
6 lengthwise extending, co-planar arrangement.

1 22. The reconfigurable article storage container
2 of Claim 17 wherein all of the first and second side ends
3 of each of the panel sections have a polygonal shape with
4 side end faces disposed at an interior angle less than 90°
5 from each other.

1 23. The reconfigurable article storage container
2 of Claim 22 further including:

3 side end connector means, releasably attachable
4 to outermost side ends of two panels, for connecting the
5 two panels in a lengthwise extending, co-planar
6 arrangement;

7 the side end connector means having first and
8 second end portions formed of spaced first and second legs,
9 the first and second legs having a shape complimentary to

10 the shape of the side ends of the panels for releasably
11 engaging the side ends of the panels; and
12 a central leg extending between the first and
13 second end portions and insertable between the outermost
14 first and second ends of two co-linearly arranged panels.

1 24. The reconfigurable article storage container
2 of Claim 22 further including:
3 vertical connector means, mountable in two
4 vertically aligned connector slots formed between a
5 connector web and one of the first and second edges of each
6 of two vertically disposed panel sections and extending
7 outward from one panel into the other panel for releasably
8 engaging and interconnecting the two panels in a stacked,
9 vertical, co-planar arrangement.

1 25. The reconfigurable article storage container
2 of Claim 24 wherein the vertical connector means
3 comprises:
4 a body having an exterior surface shaped
5 complimentary to the shape of the side end faces of the
6 panel sections to releasably engage the side end faces of
7 two edge-to-edge disposed panels.

1 26. The reconfigurable article storage container
2 of Claim 25 wherein:
3 the body has a height to engage the second
4 connector slot of one panel and the first connector slot of
5 another panel when the one and another panels are disposed
6 vertically adjacent to each other.

1 27. The reconfigurable article storage container
2 of Claim 1 wherein:
3 the side ends of each panel section have a
4 polygonal shape to form flat side end faces planarly
5 engageable with identical flat side end faces of an

6 itendical panel when two panels are interconnected in a
7 perpendicular, inverted arrangement.

1 28. The reconfigurable article storage container
2 of Claim 27 further including:

3 a vertical connector member having flat end faces
4 mountable in two vertically aligned connector slots formed
5 between a connector web and one of the first and second
6 edges of each of two vertically disposed panel sections and
7 extending outward from one panel into the other panel for
8 releasably engaging and interconnecting the two panels in
9 a stacked, vertical, co-planar arrangement.

1/4





FIG.-1



3/4




FIG. - 3




FIG.-4




FIG.-6




FIG.-5

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US93/10765

A. CLASSIFICATION OF SUBJECT MATTER

IPC(5) :B65D 6/24, 21/08

US CL :220/4.03, 4.31, 551, 552

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 220/4.03, 4.31, 551, 552

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US, A, 2,854,724 (Wuorio) 07 October 1958	All
A	US, A, 4,723,679 (Sinchok et al) 09 February 1988	All
A	US, A, 4,828,132 (Francis, Jr. et al) 09 May 1989	All
A	US, A, 5,052,580 (Khoury) 01 October 1991	All
A	US, A, 5,150,809 (Leigh) 29 September 1992	All

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be part of particular relevance	*X*	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y*	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*G*	document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means		
P document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search 21 January 1994	Date of mailing of the international search report 07 FEB 1994
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. NOT APPLICABLE	Authorized officer <i>Stephen P. Garbe</i> STEPHEN P. GARBE Telephone No. (703) 308-1207